

**Order code APEX 9000 Electro pneumatic positioner, Explosion proof**

**A= Prefix**

- AX Automax
- AC Accord
- WC Worcester Controls


**B= Model**

- 90 Digital Positioner, Single button Interface, LED Status
- 92 Digital Positioner, Full LCD Menu, LED Status


**C= Approvals, Certifications**

- E Explosion ATEX/FM

--

**D= Connections Air, Electrical**

- M 1/4" NPT air - M20 x 1,5 electrical
- N 1/4" NPT air - 1/2" NPT Electrical


**E= Housing / Surface treatment**

- U Aluminium / Powder Epoxy / Black
- R Prepared for remote mounted feedback
- S Stainless steel , Explosion proof (N connections only)


**F= Function**

- S Single Acting

--

**G= Shaft**

- 23 Namur shaft Rotary

--

**E= Cover (no indicator option on Explosion proof version)**

- 1 Flat top, no indicator

--

**F= Temperature / Seals**

- Z Standard -20C to +85C (-4F to 185F)
- Q Low temperature -40C to +85C (-40F to 185F)


**G= Input signal / Protocol**

- N 4-20mA / None
- H 4-20mA / HART


**H= Feedback options**

- X No feedback option
- T 4-20 mA transmitter only


**I= Feedback Options, Add in Electronics**

- 0 Standard Diagnostics
- 1 Advanced, built in pressure sensors (Model 92 only)


**J= Accessories**

- X 2 x gauge ports, plugged
- M 1 x gauge 0-11 bar stainless/brass
- N 2 x gauge 0-11 bar stainless/brass


<b>A</b>	<b>B</b>	<b>C</b>	<b>D</b>	<b>E</b>	<b>F</b>	<b>G</b>	<b>H</b>	<b>I</b>	<b>J</b>
----------	----------	----------	----------	----------	----------	----------	----------	----------	----------