

## D20 Explosion Proof Digital Positioner Order Code

**A = Model no**

- D 2 0 Digital compact positioner, Single button interface, LED status
- D 2 2 Digital positioner, full LCD menu, LED status

D20E	D22E

**B = Approval, Certificate**

- E Explosion proof ATEX

--	--

**C = Connections Air, Electrical**

- G 1/4" G air, M20 x 1,5 electrical x 2
- M 1/4" NPT air, M20 x 1,5 electrical x 2
- N 1/4" NPT air, 1/2" NPT electrical x 2


**D = Housing/Surface treatment**

- U Alu./Powder epoxy, black
- R Alu./Powder epoxy, black, Prepared for remote mounted feedback sensor
- S Explosion proof Stainless steel enclosure (C=N only)


**E = Function**

- S Single acting

--	--

**F = Mounting options / Spindle**

- 0 9 Double D type 6 mm, adaptor spindle (01/06/26/30/36)
- 1 2 D-style+ nut, Flowtop direct mounting (30144)
- 2 3 VDI/VDE 3845 rotary, (Mounting kit not included)
- 3 0 Adaptor spindle, select between 01/02/06/21/26/30/36
- 3 9 IEC 534-6, D style + nut. (Mounting kit not included)


**G = Cover Coulor**

- P V B PMV, Black cover, No indicator
- F S W Flowserve White, No indicator
- F S Y Flowserve Yellow, No indicator


**H = Temperature/seals**

- Z Standard -20°C to 85°C (-4°F to 185°F)
- Q Low temp -40°C to 85°C (-38°F to 185°F)


**I = Input signal/Protocol**

- 4 4-20 mA / none
- 5 4-20 mA, / HART
- P Profibus PA
- F Foundation Fieldbus


**J = Feedback option, 4-20 mA transmitter, switches**

- X No feedback option
- T 4-20 mA transmitter, Alarm output



**K = Options, Add in electronics**

- 0 Standard diagnostics
- 1 Advanced, Built in pressure sensors


**L = Accessories**

- X No accessories (gauge ports included)
- M Gauge block 1/8" G (2 x gauges included)
- N Gauge block 1/8" NPT (2 x gauges included)


**A A A B C D - E F F G G G - H I J K L**

 Consult factory